

## COVALENCE<sup>®</sup> S1137 FILLER

<b>Characteristics:</b>	S1137 is a high viscosity sealant based filler material delivered on rolls.
<b>Applications:</b>	S1137 is used as a filler material with PERP. Filler tape is used to fill the holiday thus restoring the mill applied coating thickness of the pipe.
<b>Product description:</b>	<b>S1137-XXXxYYYxZZZ</b> XXX = Width in mm YYY = Thickness in mm ZZZ = Length in mm
<b>Material properties:</b>	Typical Softening point : 150°C Typical Shear strength @ 23°C (73.4°F): 0.1 N/mm <sup>2</sup> acc. EN12068 Typical Peel strength @ 23°C (73.4°F): 1.1 N/mm acc. EN12068
<b>Dimensions:</b>	Width: 50 mm (2") Thickness: 3 mm ( 0.12") Length per roll: 3000 mm (9.8 ft)
<b>Product printing &amp; labeling:</b>	No printing. Standard box label mentioning: Covalence Description , Part Number, Lot number, Quantity
<b>Ordering info:</b>	S1137-50x3x3000 (C6): 6 rolls per box. For PERP the filler needs to be ordered separately.

### Information

<b>Documentation</b>	Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our head office, from our local distributor or by sending an email to <a href="mailto:info@sealforlife.com">info@sealforlife.com</a>
<b>Certified staff</b>	Application of the described coating system should be carried out by certified personnel.