

POLYKEN® 1027-ISO

Product Information

Product description: Polyken® liquid adhesive systems are recommended for use with only Polyken® coating systems. The liquid adhesive systems consist of butyl based elastomers blended with polymeric resins dissolved in an organic solvent system. They can be used for hand brush applications and conform to local national standards.

The Polyken 1027-ISO Liquid adhesive system is ideal for hand brush application to rough, reconditioned, or grit-blasted pipe surfaces. It provides a uniformly smooth, instant tack surface for Polyken® coating systems.

Caution:

- Store away from heat source. Read all label instructions prior to use.
- Properly stored, all Polyken® liquid coating systems have a shelf life of 3 years. Please request an application specification and storage guideline from Seal For Life.
- Polyken® liquid adhesive systems are FLAMMABLE MIXTURES.

Product properties of Polyken® 1027-ISO

Property	Typical values Units
Description	# 1027-ISO
Base	Rubber/Resins
Solvent	See Safety Data Sheet (SDS)
Total Solids	30 %
Weight/Liter	0.81 kg
Viscosity	Medium Syrup
Flash Point	Closed cup: 6°C (42.8°F)
Color	Black
VOC	0.59 kg/l
Shelf life	3 years
Coverage rate (estimated/varies)	7.4 m²/liter

Product selection guide

Max. operating temperature	85°C (185°F)
Additional mechanical layer	Subsequent Polyken coating systems
Compatible line coatings	Carbon steel, PE, FBE, PP, CTE, Tape,
Recommended pipe preparation	SSA-ST2 (SSPC-SP3) or SSA-SA 2 (SSPC-SP6) 1 – 3 mil anchor profile (25 – 76 micron anchor profile)
Performance	AWWA, DIN, EN, ISO standards

Ordering information

Item number	Description
583851-000	1027-ISO LIQUID ADH 1L (C12)
115335-000	1027-ISO LIQUID ADH 10L
14210-000	1027-ISO LIQUID ADH 200L

For other ordering options please contact your Seal For Life representative.

Application instruction: Job preparation		Handling and commissioning	
Tools, equipment and auxiliaries	Temperature gauge, DFT/WFT gauge Primer application equipment/agitator,	Exposure to loads	Objects coated with Polyken® 1027-ISO should not be exposed to loads e.g. from supports- or lifting equipment.
Additional coating materials	Subsequent Polyken coating systems, 933-25, 931, 939	Backfill	Backfill is possible immediately after completion of the coating application and after the subsequent Polyken coating system has been applied. Consult application guidelines for specific instructions. Backfill should be clean and not contain any foreign items that can cause damage to the coating system.
High humidity	Polyken® 1027-ISO can be applied in a humid atmosphere. The substrate should be free from condensing water which can be reached by keeping the temperature at least 5°F (3°C) above dew point.	Information	
Work area and substrate	The substrate surface should be dry, clean and protected against negative weather influences.	Documentation	Extensive information is available on our web-site. Application instructions and other documentation can be obtained by contacting our offices, from our local distributor or by sending an email to info@sealforlife.com
Product conditions	The Polyken® 1027-ISO shall be stored and/or transported in a dry, ventilated location. Storage temperature shall be a minimum of 60°F (16°C) and a maximum of 125°F (52°C). The minimum primer temperature for application will be 60°F (16°C).	Certified staff	Application of the described coating system shall be carried out by certified personnel.
Application instruction: Surface preparation			
General	The area to be coated has to be clean, dry, and free from oil, grease and dust. All contamination including mill-scale has to be removed.		
Degreasing	Degrease surfaces with Toluene or Heptane and e.g. a lint-free cloth.		
Preventing condensation of water	Prior to and during the application, the temperature of the substrate(s) must be at least 5°F (3°C) above the dew point.		
Substrate temperature	Temperature of the substrate should preferably be between +68°F and +104°F (+20°C / +40°C). Preheating may be required.		
Application instruction: Brief version			
Step 1	Clean substrate to SSA-ST2, SSPC-SP3 (power wire brush) or SSA-SA 2, SSPC-SP6 (commercial blast). Surface (anchor) profile depth shall be no less than 1.0 mils (25 micron) and no greater than 3 mils (76 micron).		
Step 2	Uniform primer application achieving 2 to 3 mil WFT. Primer should be "dry to touch" before application of inner layer.		

* For further detailed information, please view the corresponding Application Guideline *



SEALFORLIFE
Industries

Seal For Life Industries - Stopaq B.V.
Stadskanaal, the Netherlands
Tel: +31 599 696 170

Seal For Life Industries BV
Westerlo, Belgium
Tel: +32 14 722 500

Seal For Life Industries US LLC
San Diego, USA
Tel: +1 858 633 9785

Seal For Life Industries Mexico
S de R.L. de C.V.
Tijuana, Mexico
US Tel: +1 858 633 9785
MX Tel: +52 664 647 4300

Seal For Life India Private Ltd.
Baroda, India
Tel: +91 2667 264 721

Further information is available on our website www.sealforlife.com, or by sending an inquiry to info@sealforlife.com

DISCLAIMER: Seal For Life Industries warrants that the product conforms to its chemical and physical description and is appropriate for the use stated on the technical data sheet when used in compliance with Seal For Life Industries' written instructions. Because many installation factors are beyond the control of Seal For Life Industries, the user shall determine the suitability of the products for the intended uses and assume all risks and liabilities in connection herewith. Seal For Life's liability is stated in its General Terms and Conditions of Sale. Seal For Life Industries makes no other warranty either express or implied. All information contained in this document is to be used as a guide and is subject to change without notice. This technical data sheet supersedes all previous data sheets on this product.